Hydrogen Machines
hydrogenmachinesusa.com · hydrogenmachines.com.au
hello@hydrogenmachinesusa.com · WhatsApp +61 449 703 635

HERO Inhaler Pro 4200

Specification sheet · Professional Series



2,800 ml/min hydrogen · 99.99% purity

Our highest-output inhaler, built for multi-user clinics and wellness centres. Hydrogen and oxygen are produced as separate streams.

- **Professional Series build:** aluminium housing on castor wheels
- **Touchscreen control**
- **Two finishes:** white or black

General wellness device. Not FDA-approved; no medical claims are made.

Technical specifications

Specification	Value
Total gas output (H_2 + O_2)	4,200 ml/min
Hydrogen output	2,800 ml/min
Oxygen output	1,400 ml/min
Hydrogen purity	99.99%
Input power	100–240 V, 50/60 Hz universal input
Water requirement	Distilled or purified water, TDS < 30 ppm
Water tank	3 L
Controls	Touchscreen
Housing	Aluminium, castor wheels
Finish	White or black
Dimensions (W × D × H)	320 × 340 × 490 mm
Weight (net)	19 kg
Package dimensions (W × D × H)	430 × 410 × 675 mm
Shipping weight (packed)	21 kg
Certifications	CE (EMC and LVD), RoHS, FCC; manufactured under ISO 9001 and ISO 13485
Warranty	24 months

Operation and care

1. **Placement:** a standard power outlet (100–240 V) in a ventilated room. No plumbing or installation is needed.
2. **Water:** fill the 3-litre tank with distilled or RO-purified water only (TDS below 30 ppm). Tap water damages the electrolysis cell and voids the warranty.
3. **Between clients:** cannulas are single-client consumables; wipe down the housing after each session.
4. **Extended shutdown:** drain the tank first.

Warranty, delivery and support

Warranty	24 months from delivery. Replacement parts are shipped directly to you.
Returns	90 days
Delivery	Free UPS delivery with tracking, duties and taxes paid, to the USA and Australia. Within 14 business days.
Clinic and multi-unit pricing	Contact hello@hydrogenmachinesusa.com or WhatsApp +61 449 703 635